

Industrial self cleaning filters

BACKWASHABLE SELF CLEANING FILTERS

FILBLANC FBC-4000-02-3RS

[Download technical drawing PDF](#)



TECHNICAL FEATURES

Type	FILBLANC FBC-4000-02-3RS
Material	FRP (Fiberglass)
N. basket - Height	6x20 "
Continuous flow	No
Micron	50, 80, 125, 200, 300, 500, 800
Efficiency	90%
Efficiency on non compressible particles	High
Efficiency on compressible particles	Good
Efficiency on light particles	Good

DESIGN DATA

Min working pressure	1 bar
Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50°C
pH min	5
pH max	9
Max diameter inlet particles	3 mm
Max total suspended solids	50 mg/l (50-80 Micron) 100 mg/l (125-200-300-500-800 Micron)
Max pressure difference	2 bar

POWER

SCOPE OF USE

Water
Sea water

Industrial self cleaning filters

BACKWASHABLE SELF CLEANING FILTERS

FILBLANC FBC-4000-02-3RS

APPLICATIONS

- Prefiltration for water treatment plants
- Process water
- Evaporative cooling towers
- Heat exchangers
- Irrigation
- Aquaculture
- Protection of spray nozzles
- Prefiltration for ultrafiltration (UF) plants
- Prefiltration for reverse osmosis (RO) plants

Code	Description	Filtering surface	Height	Connecti on drain	Micron	Flow rate	Cleaning flow rate at 2 bar(m3/h)"	Cleaning time (sec)	Euro/each
FBC40003RSFRP062050WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	50	108.000	108,00	10	Login
FBC40003RSFRP062080WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	80	108.000	108,00	10	Login
FBC40003RSFRP0620125WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	125	108.000	108,00	10	Login
FBC40003RSFRP0620200WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	200	108.000	108,00	10	Login
FBC40003RSFRP0620300WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	300	108.000	108,00	10	Login
FBC40003RSFRP0620500WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	500	108.000	108,00	10	Login
FBC40003RSFRP0620800WH	FILBLANC FBC-4000-02-3RS	1.32 m ²	6x20 "	1 "	800	108.000	108,00	10	Login



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS, ARTICLES: 4.1 LETTER (a) (ii); 4.3; 13.1

Industrial self cleaning filters

BACKWASHABLE SELF CLEANING FILTERS

FILBLANC FBC-4000-02-3RS

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

SELF CLEANING FILTERS CODE LIST

Model	Material	Connection IN/OUT	Micron	Specs and finishing
FBC40003RS	FRP (Fiberglass) FRP	6x20 " 0620	50 µm 50 80 µm 80 125 µm 125 200 µm 200 300 µm 300 500 µm 500 800 µm 800	White WH



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure
Flow rate chart available on www.everblue.it by choosing microns gradient and connections and selecting specific product data sheet*