

Industrial self cleaning filters

BACKWASHABLE SELF CLEANING FILTERS

FILMAX FMX-4000-01-2RS

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FILMAX FMX-4000-01-2RS
Material	PA (Polyamide)
N. basket - Height	2x20 "
Continuous flow	No
Micron	50, 80, 125, 200, 300, 500, 800
Efficiency	90%
Efficiency on non compressible particles	Heigh
Efficiency on compressible particles	Good
Efficiency on light particles	Good

DESIGN DATA

Min working pressure	1 bar
Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	50°C
pH min	5
pH max	9
Max diameter inlet particles	3 mm
Max total suspended solids	50 mg/l (50-80 Micron) 100 mg/l (125-200-300-500-800 Micron)
Max pressure difference	2 bar

POWER

SCOPE OF USE

Water
Sea water

Industrial self cleaning filters

BACKWASHABLE SELF CLEANING FILTERS

FILMAX FMX-4000-01-2RS

APPLICATIONS

Prefiltration for water treatment plants

Process water

Evaporative cooling towers

Heat exchangers

Irrigation

Aquaculture

Protection of spray nozzles

Prefiltration for ultrafiltration (UF) plants

Prefiltration for reverse osmosis (RO) plants

Code	Description	Filtering surface	Height	Micron	Flow rate	Cleaning flow rate at 2 bar(m3/h)"	Cleaning time (sec)	Euro/each
FMX40002RSPA022050	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	50	54.000	54,00	10	Login
FMX40002RSPA022080	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	80	54.000	54,00	10	Login
FMX40002RSPA0220125	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	125	54.000	54,00	10	Login
FMX40002RSPA0220200	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	200	54.000	54,00	10	Login
FMX40002RSPA0220300	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	300	54.000	54,00	10	Login
FMX40002RSPA0220500	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	500	54.000	54,00	10	Login
FMX40002RSPA0220800	FILMAX FMX-4000-01-2RS	0.4 m ²	2x20 "	800	54.000	54,00	10	Login



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS, ARTICLES: 4.1 LETTER (a) (ii); 4.3; 13.1

Industrial self cleaning filters

BACKWASHABLE SELF CLEANING FILTERS

FILMAX FMX-4000-01-2RS

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

SELF CLEANING FILTERS CODE LIST

Model	Material	Connection IN/OUT	Micron
FMX40002RS	PA (Polyamide) PA	2x20 " 0220	50 µm 80 µm 125 µm 200 µm 300 µm 500 µm 800 µm



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure
 Flow rate chart available on www.everblue.it by choosing microns gradient and connections and selecting specific product data sheet*