

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FILTERBLACK FBK-02-4RS

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FILTERBLACK FBK-02-4RS
Material	AISI 316 L
In/Out	DN 150 FLANGE EN1092

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

SCOPE OF USE

Water

CARTRIDGES

N° cartridges	8
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FBK4RS316LBL0820M	FILTERBLACK FBK-02-4RS 8x20"	Ceramic blasted	20"	DN 150 FLANGE EN1092	BL	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FILTERBLACK FBK-02-4RS

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBK4RS	AISI 316 L 316L	BL BL	8 08	20" 20	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the directive P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned as shown in the following:

- Article n. 13
- Article n. 4

Design code: ASME VIII