

Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTERBLUE FBL-03-2RS

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FILTERBLUE FBL-03-2RS
Material	FRP (Fiberglass)
In/Out	DN 125 FLANGE DN8063 PN16

MATERIAL

Body	FRP
End plug	PVC
In-Out	POM
Drain/Vent	POM

DESIGN DATA


Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartridges	6
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FBL2RSFRPBL0620WH	FILTERBLUE FBL-03-2RS 6x20"	White	20"	DN 125 FLANGE DN8063 PN16	BL	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTERBLUE FBL-03-2RS

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBL2RS	FRP (Fiberglass) FRP	BL BL	6 06	20" 20	White WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1

Design code: BS EN 13923 2005