

Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTERBLUE MAXI-BL-21

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FILTERBLUE MAXI-BL-21
Material	FRP (Fiberglass)
In/Out	DN300 FLANGE EN1092

MATERIAL

Body	FRP
Heads	FRP
In/Out	FRP
Drain/Vent	FRP

DESIGN DATA


Max working pressure	6 bar
Hydraulic test pressure	7.8 bar
Max working temperature	50 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartridges	21
Type end caps	BL
Inner diameter min	90 mm
Outer diameter	200 mm
Cartridges height	20"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FBLMFRPBL2120WH	FILTERBLUE MAXI-BL-21 21x20"	White	20"	DN300 FLANGE EN1092	BL	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant BlueBot available on the [homepage](#).

Housings for filter cartridges

FIBERGLASS HOUSINGS

FILTERBLUE MAXI-BL-21

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FBLM	FRP (Fiberglass)	BL BL	21 21	20" 20	White WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13

Design code: EN 13121-3