

Housings for filter cartridges

POLYAMIDE HOUSINGS

FILTERMAX FMX-01-3RS

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FILTERMAX FMX-01-3RS
Material	PA (Polyamide)
In/Out	19" DN110 FLANGE DN8063 PN16

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Burst pressure	20 bar
Max working temperature	40 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartridges	3
Type end caps	MX
Inner diameter min	70 mm
Outer diameter	160 mm
Cartridges height	20"



Code	Description	Cartridges	In/Out	End cap	Euro/each
FMX3RSPAMX0320	FILTERMAX FMX-01-3RS 3x20"	20"	19" DN110 FLANGE DN8063 PN16	MX	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

POLYAMIDE HOUSINGS

FILTERMAX FMX-01-3RS

HOUSINGS CODE LIST

Model	Material		Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
FMX3RS	PA (Polyamide)	PA	MX	MX	3	03	20"	20		



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13