

# Housings for filter cartridges

## POLYAMIDE HOUSINGS

### FILTERMAX FMX-01-4RS

[Download technical drawing PDF](#) 

#### TECHNICAL FEATURES

Type	FILTERMAX FMX-01-4RS
Material	PA (Polyamide)
In/Out	19" DN110 FLANGE DN8063 PN16

#### DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Burst pressure	20 bar
Max working temperature	40 C°

#### SCOPE OF USE

Water
Sea water

#### CARTRIDGES

N° cartridges	4
Type end caps	MX
Inner diameter min	70 mm
Outer diameter	160 mm
Cartridges height	20"



Code	Description	Cartridges	In/Out	End cap	Euro/each
FMX4RSPAMX0420	FILTERMAX FMX-01-4RS 4x20"	20"	19" DN110 FLANGE DN8063 PN16	MX	<a href="#">Login</a>

*For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).*

# Housings for filter cartridges

## POLYAMIDE HOUSINGS

### FILTERMAX FMX-01-4RS

**HOUSINGS CODE LIST**

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMX4RS	PA (Polyamide) PA	MX MX	4 04	20" 20	



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*



**European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13