

Housings for filter cartridges

POLYAMIDE HOUSINGS

FILTERMAX FMX-01

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FILTERMAX FMX-01
Material	PA (Polyamide)
In/Out	2" BSP M,3" BSP M

DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Burst pressure	20 bar
Max working temperature	40 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartridges	1
Type end caps	MX
Inner diameter min	70 mm
Outer diameter	160 mm
Cartridges height	13",20"



Code	Description	Cartridges	In/Out	End cap	Euro/each
FMXPAMX0113	FILTERMAX FMX-01 1x13"	13"	2" BSP M	MX	Login
FMXPAMX0120	FILTERMAX FMX-01 1x20"	20"	3" BSP M	MX	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

POLYAMIDE HOUSINGS

FILTERMAX FMX-01

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMX	PA (Polyamide) PA	MX MX	1 01	13" 20" 13 20	



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13