

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FM0-BHF

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FM0-BHF
Material	AISI 316 L
In/Out	1" 1/2 BSP M

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

SCOPE OF USE

Water

CARTRIDGES

N° cartridges	1
Type end caps	FilterBig
Inner diameter min	36 mm
Outer diameter	115 mm
Cartridges height	9" 3/4,20"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FM0316LBHF0109M	FM0-BHF 1x9" 3/4	Ceramic blasted	9" 3/4	1" 1/2 BSP M	BHF	Login
FM0316LBHF0120M	FM0-BHF 1x20"	Ceramic blasted	20"	1" 1/2 BSP M	BHF	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant BlueBot available on the [homepage](#).

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FM0-BHF

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FM0	AISI 316 L 316L	FilterBig BHF	1 01	9" 3/4 20"	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1