

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FM0

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FM0
Material	AISI 316 L
In/Out	3/4" BSP M

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	15 bar
Max working temperature	50 C°

SCOPE OF USE

Water

CARTRIDGES

N° cartridges	1
Type end caps	DOE (Standard)
Inner diameter min	27 mm
Outer diameter	70 mm
Cartridges height	9" 3/4, 20", 30", 40"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FM0316LST0109M	FM0 1x9" 3/4	Ceramic blasted	9" 3/4	3/4" BSP M	ST	Login
FM0316LST0120M	FM0 1x20"	Ceramic blasted	20"	3/4" BSP M	ST	Login
FM0316LST0130M	FM0 1x30"	Ceramic blasted	30"	3/4" BSP M	ST	Login
FM0316LST0140M	FM0 1x40"	Ceramic blasted	40"	3/4" BSP M	ST	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FM0

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FM0	AISI 316 L 316L	DOE (Standard) ST	1 01	9" 3/4 20" 30" 40" 09 20 30 40	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU
 FLUID: NOT DANGEROUS
 4.1 LETTER (a) (ii)
 4.3
 13.1