

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FMC-07

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	FMC-07
Material	AISI 316 L
In/Out	2" 1/2 BSP M

DESIGN DATA

Max working pressure	8 bar
Hydraulic test pressure	12 bar
Max working temperature	80 C°

SCOPE OF USE

Water

CARTRIDGES

N° cartridges	7
Type end caps	DOE (Standard)
Inner diameter min	26 mm
Outer diameter	68 mm
Cartridges height	20",30",40"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FMC316LST0720M	FMC-07 7x20"	Ceramic blasted	20"	2" 1/2 BSP M	ST	Login
FMC316LST0730M	FMC-07 7x30"	Ceramic blasted	30"	2" 1/2 BSP M	ST	Login
FMC316LST0740M	FMC-07 7x40"	Ceramic blasted	40"	2" 1/2 BSP M	ST	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

STAINLESS STEEL SS 316 L HOUSINGS

FMC-07

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMC	AISI 316 L 316L	DOE (Standard) ST	7 07	20" 30" 40" 20 30 40	Ceramic blasted M



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

COUNTRY OF ORIGIN: Italy



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1