

## Housings for filter cartridges

# STAINLESS STEEL SS 316 L HOUSINGS

## FMR-60

[Download technical drawing PDF](#) 

### TECHNICAL FEATURES

Type	FMR-60
Material	AISI 316 L
In/Out	DN 200 FLANGE L

### DESIGN DATA

Max working pressure	6 bar
Hydraulic test pressure	9 bar
Max working temperature	80 C°

### SCOPE OF USE

Water

### CARTRIDGES

N° cartridges	60
Type end caps	DOE (Standard)
Inner diameter min	26 mm
Outer diameter	68 mm
Cartridges height	40"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
FMR316LST6040DP	FMR-60 60x40"	Pickled, Passivated	40"	DN 200 FLANGE L	ST	<a href="#">Login</a>

*For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).*

## Housings for filter cartridges

# STAINLESS STEEL SS 316 L HOUSINGS

## FMR-60

### HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
FMR	AISI 316 L 316L	DOE (Standard) ST	60 60	40" 40	Pickled, Passivated DP



*Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure*



**European Community members only.**

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1

**Design code:** EN 13445-3-4-5