

Pleated filtration cartridges

PLEATED POLYPROPYLENE CARTRIDGE

PP95OR5L200

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	PP95OR5L200
Type	Pleated polypropylene
Height	60"
Micron	1 / 5 / 10 / 20 / 50
Efficiency	95%
Hot sanitizing	No

MATERIAL

Filtration material	Polypropylene
Internal core	Polypropylene
External core	None

PRESSURE

Max differential pressure at 20°C	2 bar
Recommended change-out differential pressure	1 bar

TEMPERATURE

Max working temperature	50°C
-------------------------	------

SCOPE OF USE

Water
Sea water



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

Code	Height	Micron	Flow l/h	¹	Filtering surface	Quantity box	Euro/each
PP95OR5L2006001ORS	60"	1	36.000		10,60 m ²	1	Login
PP95OR5L2006005ORS	60"	5	54.000		10,60 m ²	1	Login
PP95OR5L2006010ORS	60"	10	54.000		10,60 m ²	1	Login
PP95OR5L2006020ORS	60"	20	54.000		10,60 m ²	1	Login
PP95OR5L2006050ORS	60"	50	54.000		10,60 m ²	1	Login

¹ Max water flow rate at 20°C and differential pressure 0,15 bar

Pleated filtration cartridges

PLEATED POLYPROPYLENE CARTRIDGE

PP95OR5L200

END CAPS LIST

End Caps	OR
CODE	OR



CARTRIDGES CODE LIST

Model	Height		Micron		Connection		Seals	
PP95OR5L200	60"	60	1 5 10 20 50	01 05 10 20 50	OR	OR	Silicone	S

* standard o-ring


Pleated filtration cartridges

PLEATED POLYPROPYLENE CARTRIDGE

PP95OR5L200

FLOW RATE VS PRESSURE DIFFERENTIAL

Pressure differential



Graphic refers to 60" height cartridges. Make the correct proportion to obtain flow for taller cartridges.