

Housings for filter cartridges

PVC HOUSINGS

RIFBLUE PVC RIF-01-2RS

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	RIFBLUE PVC RIF-01-2RS
Material	PVC (Polyvinyl chloride)
In/Out	DN 32 FLANGE F

DESIGN DATA

Max working pressure	8 bar
Hydraulic test pressure	12 bar
Max working temperature	50 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartridges	2
Type end caps	RIF
Outer diameter	70 mm
Cartridges height	30"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
RIF02RSPVC RIF0230WH	RIFBLUE PVC RIF-01-2RS 2x30"	White	30"	DN 32 FLANGE F	RIF	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant BlueBot available on the [homepage](#).

Housings for filter cartridges

PVC HOUSINGS

RIFBLUE PVC RIF-01-2RS

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
RIF02RS	PVC (Polyvinyl chloride)	RIF	RIF	2	02	30"	30	White	WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13