

Housings for filter cartridges

PVC HOUSINGS

RIFBLUE PVC RIF-01

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	RIFBLUE PVC RIF-01
Material	PVC (Polyvinyl chloride)
In/Out	DN 25 D 32 1" BSP F / D. 32 (DN 25 / D. 32)

DESIGN DATA

Max working pressure	8 bar
Hydraulic test pressure	12 bar
Max working temperature	50 C°

SCOPE OF USE

Water
Sea water

CARTRIDGES

N° cartridges	1
Type end caps	RIF
Outer diameter	70 mm
Cartridges height	10",20",30"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
RIFPVCRIFF0110WH	RIFBLUE PVC RIF-01 1x10"	White	10"	DN 25 D 32 1" BSP F / D. 32 (DN 25 / D. 32)	RIF	Login
RIFPVCRIFF0120WH	RIFBLUE PVC RIF-01 1x20"	White	20"	DN 25 D 32 1" BSP F / D. 32 (DN 25 / D. 32)	RIF	Login
RIFPVCRIFF0130WH	RIFBLUE PVC RIF-01 1x30"	White	30"	DN 25 D 32 1" BSP F / D. 32 (DN 25 / D. 32)	RIF	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant BlueBot available on the [homepage](#).

Housings for filter cartridges

PVC HOUSINGS

RIFBLUE PVC RIF-01

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type		Cartridges n°		Cartridges height		Specs and finishing	
RIF	PVC (Polyvinyl chloride)	RIF	RIF	1	01	10" 20" 30"	10 20 30	White	WH



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13