

Housings for filter cartridges

STAINLESS STEEL SS 316 HOUSINGS L

SH0-C7-08

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	SH0-C7-08
Material	AISI 316 L
In/Out	1" 1/2 CLAMP, 2" CLAMP, 2" 1/2 CLAMP

DESIGN DATA

Max working pressure	10 bar
Hydraulic test pressure	14.3 bar
Max working temperature	80 C°

SCOPE OF USE

Water

CARTRIDGES

N° cartridges	8
Type end caps	Code 7
Outer diameter	70 mm
Cartridges height	20", 30", 40"



Code	Description	Specs, colors and particular finishing	Cartridges	In/Out	End cap	Euro/each
SH0316LC70820R112TC	SH0-C7-08 8x20"	Mechanical polishing (RA < 0,8 µm) 1" 1/2 Clamp	20"	1" 1/2 CLAMP	C7	Login
SH0316LC70820R200TC	SH0-C7-08 8x20"	Mechanical polishing (RA < 0,8 µm) 2" Clamp	20"	2" CLAMP	C7	Login
SH0316LC70820R212TC	SH0-C7-08 8x20"	Mechanical polishing (RA < 0,8 µm) 2" 1/2 Clamp	20"	2" 1/2 CLAMP	C7	Login
SH0316LC70830R112TC	SH0-C7-08 8x30"	Mechanical polishing (RA < 0,8 µm) 1" 1/2 Clamp	30"	1" 1/2 CLAMP	C7	Login
SH0316LC70830R200TC	SH0-C7-08 8x30"	Mechanical polishing (RA < 0,8 µm) 2" Clamp	30"	2" CLAMP	C7	Login
SH0316LC70830R212TC	SH0-C7-08 8x30"	Mechanical polishing (RA < 0,8 µm) 2" 1/2 Clamp	30"	2" 1/2 CLAMP	C7	Login
SH0316LC70840R112TC	SH0-C7-08 8x40"	Mechanical polishing (RA < 0,8 µm) 1" 1/2 Clamp	40"	1" 1/2 CLAMP	C7	Login
SH0316LC70840R200TC	SH0-C7-08 8x40"	Mechanical polishing (RA < 0,8 µm) 2" Clamp	40"	2" CLAMP	C7	Login
SH0316LC70840R212TC	SH0-C7-08 8x40"	Mechanical polishing (RA < 0,8 µm) 2" 1/2 Clamp	40"	2" 1/2 CLAMP	C7	Login

For determining the flow rate, we recommend using the calculation software [Everblue Selector](#) or consulting our virtual assistant [BlueBot](#) available on the [homepage](#).

Housings for filter cartridges

STAINLESS STEEL SS 316 HOUSINGS L

SH0-C7-08

HOUSINGS CODE LIST

Model	Material	Cartridges end cap type	Cartridges n°	Cartridges height	Specs and finishing
SH0	AISI 316 L 316L	Code 7 C7	8 08	20" 30" 40"	20 30 40 Mechanical polishing (RA < 0,8 µm) 1"1/2 Clamp Mechanical polishing (RA < 0,8 µm) 2" Clamp Mechanical polishing (RA < 0,8 µm) 2"1/2 Clamp



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure



European Community members only.

These filters are free of the "CE" stamp since they are included in the article n. 4 para 3 of the P.E.D. 2014/68/EU of 15 May 2014. These filters can be used only with the fluid and design that respect the conditions established by the directive above mentioned.

PED REFERENCES: PED 2014/68/EU

FLUID: NOT DANGEROUS

ARTICLES: 4.1 LETTER (a) (ii)

4.3

13.1