

Washable filtration cartridges

PLEATED POLYESTER NET CARTRIDGE

TPL95BLF200

[Download technical drawing PDF](#) 

TECHNICAL FEATURES

Type	TPL95BLF200
Type	Pleated polyester sleeve
Height	20"
Micron	20 / 50
Efficiency	95%
Hot sanitizing	No

MATERIAL

Filtration material	Polyester
Internal core	Polypropylene - FILSTAR INSIDE
External core	None

PRESSURE

Max differential pressure at 20°C	3 bar
Recommended change-out differential pressure	1 bar

TEMPERATURE

Max working temperature	50°C
-------------------------	------

SCOPE OF USE

Water
Sea water



Approximate picture. End caps and height's choice will lead to the assembly of a product which could differ from those shown in figure

Code	Height	Micron	Flow l/h	¹	Filtering surface	Quantity box	Euro/each
TPL95BLF2002020BLS	20"	20	18.000		2,52 m ²	1	Login
TPL95BLF2002050BLS	20"	50	18.000		2,52 m ²	1	Login

¹ Max water flow rate at 20°C and differential pressure 0,15 bar

Washable filtration cartridges

PLEATED POLYESTER NET CARTRIDGE

TPL95BLF200

END CAPS LIST

End Caps	BL
CODE	BL



CARTRIDGES CODE LIST

Model	Height		Micron		Connection		Seals
TPL95BLF200	20"	20	20 50	20 50	BL	BL	Silicone Other available orings EPDM NBR Teflon Viton
							S E N T V

* standard O-ring


Washable filtration cartridges

PLEATED POLYESTER NET CARTRIDGE

TPL95BLF200

FLOW RATE VS PRESSURE DIFFERENTIAL

Pressure differential



Graphic refers to 20" height cartridges. Make the correct proportion to obtain flow for taller cartridges.