

VNX30CDIT-2 High Flow Continuous Electrodeionization (CEDI) Modules

Operating environment

Installation should be indoors with no direct sunlight and it should have a maximum ambient temperature of 45°C (113°F).

Materials of construction

1. Wetted components of the VNX module consists of: PVC (adapters), nylon/ABS polyphenylene, silicone, ion-selective membranes, ion exchange resins and thermoplastic elastomer.
2. Polypropylene 3-part union connectors available for purchase.
3. Housing is fiberglass reinforced plastic (FRP). Standard color is white with glossy finish. Custom colors and labeling are available.
4. The bracket/end-block assembly is an epoxy painted aluminum casting suitable for securing modules to the frames and/or each other in Pure Water Group system approved configurations.

Quality Assurance Standards

CE marked. Each module is factory tested to meet strict industry standards and is manufactured in an ISO 9001 and ISO 14000 quality and environmental management system.

Halal certification: modules are manufactured in accordance with the Islamic Food and Nutrition Council of America Standards (IFANCA), and will carry the Crescent M Halal Logo.

Accessories Ordering Information

PSSW60012	DC power supply 3x400 VAC-600VDC/12A/4.8kW
CISW00108	Control Interface for communication PSSW - PLC
DSPSSW08	Control display for 1-8x PSSW
DSPSSW01	Control Display for PSSW
CSXPP3P06	Con. set VNX-2, PP-3P, 2x50DN40, 2x25DN20, 2018 version

Maximum Feed Water Specifications

Feed water conductivity equivalent, Including CO ₂ and Silica	< 100 µS/cm
Feed water source	RO permeate
Temperature	41 - 113°F (5 - 45°C)
Inlet pressure	20 - 100 psi (1.4 - 7 bar)
Maximum total chlorine (as Cl ₂)	< 0.02 ppm
Iron (Fe)	< 0.01 ppm
Manganese (Mn)	< 0.01 ppm
Sulphide (S ⁻)	< 0.01 ppm
pH	4 - 11
Total hardness (as CaCO ₃)	< 4.0 ppm
Dissolved organics (TOC as C)	< 0.5 ppm
Silica (SiO ₂)	< 2.0 ppm

Typical Module Performance

Operating Parameters

Recovery	80 - 90%
Flow rate: minimum	15 gpm (3.4 m ³ /h)
Flow rate: nominal	30 gpm (6.8 m ³ /h)
Flow rate: maximum	45 gpm (10.2 m ³ /h)
DC voltage	0 - 600

DC Amperage

0 - 1.5 ppm hardness	0 - 13.2 amps
1.5 - 2.5 ppm hardness	0 - 8 amps
2.5 - 4 ppm hardness	0 - 4 amps

Product Water Quality

Product resistivity	> 16 MΩ-cm*
Silica (SiO ₂) removal	≥ 95%
Sulphate (SO ₄) removal	≥ 99.5%
Sodium (Na) removal	≥ 99.5%
Chloride (Cl) removal	≥ 99.5%

*Actual performance may be determined using the projection software

Ordering Information and Physical Specifications

Order #	Module #	Width	Height	Length	Shipping Weight
0111000030	VNX30CDIT-2	50.8 cm (20.0")	50.8 cm (20.0")	213 cm (84.0")	473 kg (1042 lbs)

Pure Water Group
Korte Hei 3
4714 RD Sprundel
Tel. +31 165 348 253
info@purewatergroup.com
www.purewatergroup.com

longpure is a trademark of Evoqua, its subsidiaries or affiliates. The information provided in this literature contains merely general descriptions or characteristics of performance which in actual case of use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in terms and of the contract